

# MONO - DOPPIO

## EXHAUST EXTRACTION SYSTEMS



### USE

- Exhaust gas extraction for cars, motorcycles and other industrial and agricultural vehicles
- Single and centralized plants in car repair shops, overhaul and testing centers, garages, body shops, warehouses and car parks
- Exhaust gas extraction systems in both civil and industrial contexts

### FEATURES

- 0.75 kW fan also in the basic version for a higher suction power
- Very sturdy painted sheet metal structure
- Statically and dynamically balanced fan
- Wall bracket for pipe (STT) already included in the MONO and DOUBLE kits
- Flexible pipe resistant to 150 °C
- Customizations

### TECHNICAL DATA

MODEL	PIPE LENGTH m	Ø PIPE mm	Ø EXPULSION mm	POWER kW	VOLTAGE V/Hz	MAX FLOW RATE m <sup>3</sup> /h	NOISE dB(A)	WEIGHT Kg
<b>MONO75/25</b>	2,5	75	100	0,75	380 / 50	320	62	18
<b>MONO75/5</b>	5	75	100	0,75	380 / 50	320	62	20
<b>MONO100/25</b>	2,5	100	100	0,75	380 / 50	550	65	21
<b>MONO100/5</b>	5	100	100	0,75	380 / 50	550	65	24
<b>DOPPIO75/25</b>	2 x 2,5	75	100	1,1	380 / 50	500	62	20
<b>DOPPIO75/5</b>	2 x 5	75	100	1,1	380 / 50	500	62	22
<b>DOPPIO75/75</b>	2 x 7,5	75	100	1,1	380 / 50	500	62	23
<b>DOPPIO75/10</b>	2 x 10	75	100	1,1	380 / 50	500	62	24
<b>DOPPIO100/25</b>	2 x 2,5	100	100	1,1	380 / 50	1000	65	24
<b>DOPPIO100/5</b>	2 x 5	100	100	1,1	380 / 50	1000	65	27
<b>DOPPIO100/75</b>	2 x 7,5	100	100	1,1	380 / 50	1000	65	24
<b>DOPPIO100/10</b>	2 x 10	100	100	1,1	380 / 50	1000	65	27